

PVC TARPAULIN TECHNICAL DATA SHEET

PRODUCT MODEL NAME	<u>PT-900 HIGH-TECH PVC TARPAULIN</u>		
TECHNICAL SPECIFICATION	STANDARD	UNIT	VALUE
BASE FABRIC	DIN 60 001		100% PES
YARN TYPE	DIN EN ISO 2060	POLYESTER	2230 DTX
WEAVING CONSTRUCTION TYPE			6x6 (30.5x30.5)
WEIGHT	DIN EN ISO 2286/2	gr / m2	900 ± 5
WIDTH		cm	150 - 300 (Options Available)
ROLL LENGHT		mm	50 - 250 (Options Available)
SURFACE TYPE			GLOSSY-MATT
TEMPRATURE RESISTANT LOW	DIN EN 1876/1	°C	-30
TEMPRATURE RESISTANT HIGH	IVK / PKT.5	°C	+70
TENSILE STRENGHT (WARP/WEFT)	ISO 1421/1	N / 5cm	4200 / 4000
TEAR STRENGHT (WARP/WEFT)	ISO 4674/1	N	500 / 400
ADHESION	ISO 2411	N / 5cm	100
COLOUR FASTNESS	ISO 105-BO2		6+
EXTRA TREATMENT	ACRYLIC / SILVER / PVDF / LAC		UPON REQUEST
FLAMMABILITY (FR)	DIN 4102-1/ NF P 92-507		B2 / B1 / M2 (ON REQUEST)

