

PVC TARPAULIN TECHNICAL DATA SHEET

PRODUCT MODEL NAME	<u>PT-680 TRUCK PVC TARPAULIN</u>		
TECHNICAL SPECIFICATION	STANDARD	UNIT	VALUE
BASE FABRIC	DIN 60 001		100% PES
YARN TYPE	DIN EN ISO 2060	POLYESTER	1100 DTX
WEAVING CONSTRUCTION TYPE			8x8 (20x20)
WEIGHT	TS 1534 EN ISO 2286-2 DIN EN ISO 2286-2	gr / m2	680 ± 5
WIDTH		cm	150 - 250 - 300 - 320 (Options Available)
ROLL LENGHT		mm	50 - 250 (Options Available)
SURFACE TYPE			GLOSSY-MATT-EMBOSS
TEMPRATURE RESISTANT LOW	DIN EN 1876-1	°C	-30
TEMPRATURE RESISTANT HIGH	IVK / PKT.5	°C	+70
TENSILE STRENGHT (WARP/WEFT)	EN ISO 1421	N / 5cm	2500 / 2300
TEAR STRENGHT (WARP/WEFT)	EN ISO 4674-1	N	220 / 200
ADHESION	EN ISO 2411	N / 5cm	80
COLOUR FASTNESS	BS EN ISO 105-BO2		6+
EXTRA TREATMENT	ACRYLIC / SILVER / PVDF / LAC		UPON REQUEST
FLAMMABILITY (FR)	DIN 4102-1/ NF P 92-507		B2 / B1 / M2 (ON REQUEST)

